

---

# Contents

---

<b>Contents</b>	<b>xix</b>
<b>List of Figures</b>	<b>xxiii</b>
<b>List of Tables</b>	<b>xxx</b>
<b>Nomenclature</b>	<b>xxxi</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Background and context . . . . .	1
1.2 Objectives of the thesis . . . . .	4
1.3 About this thesis . . . . .	6
References . . . . .	8
<b>2 Experimental tools</b>	<b>15</b>
2.1 The fuel injection system . . . . .	15
2.2 Hydraulic characterization equipment . . . . .	15
2.3 Isothermal spray visualization test rig . . . . .	17
2.4 The high temperature and high pressure test rig . . . . .	18
2.5 Nozzles . . . . .	19
2.6 Fuels . . . . .	20
References . . . . .	22
<b>3 Hydraulic characterization</b>	<b>25</b>
3.1 Hydraulic characterization test plan . . . . .	25
3.2 Rate of injection . . . . .	26
3.3 Spray momentum . . . . .	28
3.4 Hydraulic analysis . . . . .	30

3.5	Conclusions . . . . .	32
	References . . . . .	35
<b>4</b>	<b>Isothermal spray visualization</b>	<b>37</b>
4.1	Optical technique and setup . . . . .	37
4.2	Image processing . . . . .	38
4.3	Test plan . . . . .	41
4.4	The effect of nozzle geometry on spray formation . . . . .	42
4.5	Spray formation for different fuels . . . . .	49
4.6	A further analysis on nozzle and fuel effects on spray formation, mixing and fluctuations . . . . .	50
4.7	Conclusions . . . . .	55
	References . . . . .	56
<b>5</b>	<b>Evaporative inert spray visualization</b>	<b>61</b>
5.1	Optical setup . . . . .	62
5.2	Image processing . . . . .	63
5.3	Test plan . . . . .	66
5.4	Evaporative spray development . . . . .	66
5.5	Spray tip penetration . . . . .	68
5.5.1	The effect of ambient temperature and rail pressure . . . . .	68
5.5.2	Comparing nozzles . . . . .	70
5.5.3	Comparing fuels . . . . .	74
5.6	Spray spreading angle . . . . .	74
5.7	Liquid penetration length for different nozzles and fuels . . . . .	78
5.8	Spray boundary fluctuations . . . . .	83
5.9	Conclusions . . . . .	88
	References . . . . .	90
<b>6</b>	<b>Reactive spray visualization</b>	<b>95</b>
6.1	Optical setup . . . . .	96
6.2	Schlieren image processing . . . . .	97
6.3	Test plan . . . . .	98
6.4	Reactive spray development . . . . .	99
6.5	Reactive spray tip penetration . . . . .	99
6.6	Lift-off length . . . . .	101
6.6.1	OH* chemiluminescence signals . . . . .	105
6.6.2	Parametric variations . . . . .	105
6.7	Ignition delay . . . . .	109
6.7.1	Tracer signals . . . . .	110

6.7.2	Parametric variations . . . . .	113
6.7.3	Further discussion on the effect of nozzle geometry over the SSI . . . . .	118
6.8	Conclusions . . . . .	121
	References . . . . .	121
<b>7</b>	<b>Conclusions</b>	<b>125</b>
7.1	Summary and conclusions . . . . .	125
7.2	Future direction . . . . .	127
	<b>Bibliography</b>	<b>131</b>